## **SAFETY DATA SHEET**

Date Prepared: 4/9/2014 Phury Replaces: All Previous

## **SECTION 1. IDENTIFICATION**

Product Name: Phury

Synonyms: Urea Sulfate Solution, FLO150016S

Use: Agricultural, Liquid Micronutrient Fertilizer

Manufacturer: Chemical Dynamics, Inc.

> 4206 Business Lane Plant City FL 33566

813-752-4950

Phone: Chemtrec (Emergency) Phone: 800-424-9300

SECTION 2. HAZARDS IDENTIFICATION				
Pictogram	Signal Word Hazard Class Hazard Category Hazard Stateme		Hazard Statement	
	DANGER	Skin Corrosion Eye Damage Corrosive to Metals	Cat 1	Causes severe skin burns and serious eye damage. May be Corrosive to Metals
Precautionary Statements:	Prevention: Do not breathe vapors, mists or sprays. Wash thoroughly after handling. Wear protective gloves, protective clothing, eye protection, and face protection. Keep in original container.  Response: If swallowed: rinse mouth, Do NOT induce vomiting. If on skin (or hair): Take of immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Immediately call doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call doctor.  If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  Immediately call doctor.  Absorb spillage to prevent material damage.  Storage: Store locked up. Store in corrosive resistant container (See Section 7 of SDS).			
	<b>Disposal</b> : Dispose of contents/containers in accordance with local/regional/national regulations (See Section 13 of SDS).			

## **SECTION 3. COMPOSITION**

Material CAS# %WT **EINECS # Urea Sulfate** 21351-39-3 244-343-6 79%

(Monocarbamide dihydrogensulfate)

Water 7732-18-5 231-791-2 balance

See product label for guaranteed analysis.

	SECTION 4. FIRST AID MEASURES
Ingestion:	Rinse mouth. Do NOT induce vomiting. Drink large amounts of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Skin Contact:	Immediately Take of immediately all contaminated clothing and rinse skin with water/shower. Wash contaminated clothing before reuse. Get medical attention immediately.
Inhalation:	Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Seek prompt medical attention.
Eye Contact:	Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing eyes during transport to hospital.
Acute Exposure	Harmful if swallowed or inhaled. Immediately seek medical attention.
Symptoms:	This product is corrosive to all tissues with which it comes in contact.  Contact with skin does not normally cause immediate irritation but prolonged contact may result in redness, swelling, skin burns and severe damage.  Inhalation of the vapor or mist can cause eye, nose, throat, and respiratory irritation or coughing.  When ingested, it can produce nausea, vomiting, abdominal pain, diarrhea, and irritation or burns of the oropharyngeal mucosa, esophagus, and stomach.
Chronic Exposure	Not available
Symptoms:	

	SECTION 5. FIRE FIGHTING MEASURES
Extinguishing	This product is non-flammable. Use appropriate media for surrounding fire. Cool
Media:	containers with water spray to avoid rupture due to thermal expansion.
Specific Hazards:	This product is an aqueous mixture and is not flammable. However, above 110°C (230°F), this product can vigorously decompose and release carbon dioxide. The resulting increase in pressure can rupture containers. If material is exposed to prolonged heat in a fire, material may release oxides of carbon, sulfur and nitrogen. For safety, avoid water spray with full jet to prevent spread of product.
Protective	Wear self-contained breathing apparatus (SCBA) and full protective gear. Avoid
Equipment and	inhaling combustion products.
Precautions for	Fire run-off should be contained to prevent possible environmental damage.
Fire-Fighters:	
NFPA Rating:	Health: 3, Fire: 0, Reactivity: 0

	SECTION 6. ACCIDENTAL RELEASE MEASURES
Precautions:	Corrosive liquid. Isolate area. Keep unnecessary personnel away. Avoid splashing
	or spraying. Do no touch or walk through spilled material.
Protective	Impervious gloves (rubber, neoprene or nitrile), chemical resistant suit,
Equipment:	chemical splash-proof goggles, face shield.
	Chemical resistant apron and/or rubber boots may be needed. Use NIOSH
	approved respirator if vapors or mists exceed applicable concentration limits.
Containment:	Stop flow of material if safe to do so. Dike area with diatomaceous earth or sand
	and maximize recovery. Prevent spillage from entering drains or open bodies of
	water. Any release to the environment may be subject to reporting requirements.

Clean Up:	Pump into a suitable tank or absorb with diatomaceous earth or sand. Make sure
	pumping equipment is 316L stainless steel construction. Residue can be
	neutralized slowly with lime. Recover and dispose of residue. Sweep up and place
	into suitable containers for agronomical land application at recommended rates or
	dispose of in accordance with local/regional/national regulations (See Section 13 of
	SDS).

	SECTION 7. HANDLING AND STORAGE
Precautions for safe handling:	Open containers carefully. Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Do not eat, drink or use tobacco products when handling this material. Apply product in open areas. Keep away from children and pets. Do not contaminate feed, seed or any water sources. Launder work clothes frequently and separate from other laundry.  When diluting always pour product into water and not vice versa
Conditions for safe storage:	Store locked up. Store in a well-ventilated, cool, dry place, away from sources of intense heat, or where freezing is possible. Keep away from combustible materials, strong bases and metals. Large storage tanks should have secondary containment and electrically grounded. Polyethylene, polypropylene and 316L stainless steel are acceptable materials for storage containers. Will corrode incompatible metals. Tanks should be vented and painted white or in light heat-reflecting colors. Piping should be all welded schedule 80. Ensure that all pumps, valves, meters, gaskets, etc., are of compatible materials. Periodic inspection of metallic components for corrosion should be conducted. Keep containers tightly closed when not in use. Do not let product go below 35°F. Inspect all incoming containers before storage, to ensure containers are properly labeled and not damaged.
Incompatibilities:	Avoid storage, piping or handling systems made of copper, zinc and their alloys.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION				
Component	Urea Sulfate	Not Established	PEL, OSHA	
Exposure Limits:	CH <sub>6</sub> N <sub>2</sub> O <sub>5</sub> S	Not Established	STEL, OSHA	
		Not Established	TLV, ACGIH	
		Not Established	IDLH, NIOSH	
		Not Established	REL, NIOSH	
		Not Established	STEL, NIOSH	
Engineering	Provide local exhaust v	Provide local exhaust ventilation and wash facilities. Eye wash stations and safety		
Controls:	showers required.			
Personal	Eyes: Chemical splash-proof goggles and face shield			
Protective	Skin: Impervious gloves (rubber, neoprene or nitrile), long sleeved clothing.			
Equipment:	Chemically resistant apron is recommended.			
	Respiratory: None required for ambient air concentrations (i.e. in the open under normal agronomic conditions) not exceeding occupational exposure limits.			
	Respiratory protection may be required in the event of a spill in an enclosed area.			
	Wear NIOSH approved respiratory protective equipment when vapor or mists may exist as well as a chemical suit.			

SDS: Phury Chemical Dynamics, Inc.

Rev: 4/9/2014

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES			
Appearance:	Clear, pink liquid		
Odor:	Odorless	UEL / LEL:	Not Applicable
Odor Threshold:	Not Available	Vapor Pressure:	Not Available
pH:	< 0	Density:	1.51 to 1.53 g/cm <sup>3</sup>
Melting/Freezing Point:	5.6°C (42°F) – Salt Out	Solubility:	Water
Boiling Point:	Decomposes 110°C (230°F)	Log <sub>ow</sub> :	Not Available
Flash Point:	Not Applicable	Auto Ignition Temp:	Not Applicable
<b>Evaporation Rate:</b>	Similar to water	Decomposition Temp:	110°C (230°F)
Flammability (Solid/Gas):	Not Applicable	Viscosity	Not Available

SECTION 10. STABILITY AND REACTIVITY		
Reactivity:	Product is acidic.	
Chemical Stability:	Stable under normal conditions.	
Possibility of Hazardous	Hazardous polymerization will not occur.	
Reactions:		
Conditions to avoid:	High temperatures. May vigorously decompose under high temperature conditions, >110°C (230°F) releasing carbon dioxide gas and rupture containers.	
Incompatible Materials:	Reactive or incompatible with nitrates, hypochlorites, sulfides, alkaline materials and many metals. Toxic or flammable gases may be formed. Do not mix with UAN solutions.  Extremely corrosive to copper, aluminum, zinc. Corrosive to mild steel.  Slightly corrosive to 316 stainless steel. Incompatible with nylon or nylon blends. Acceptable container materials are fiberglass, CPVC, polyethylene, polypropylene or 316L stainless steel. Consult a metallurgist for compatibility with handling equipment and periodic inspection of metal components.	
Hazardous	Carbon dioxide.	
<b>Decomposition Products:</b>		

SECTION 11. TOXILOGICAL INFORMATION		
Acute Toxicity:	LD50 oral (rat): 350 mg/kg	
	LD50 dermal (rabbit): >2000 mg/kg	
Likely Routes of	Inhalation of mist, eye, and skin contact.	
Exposure:		
Symptoms and Signs of	Eyes: Contact causes severe irritation and tissue damage; Eye burns,	
Exposure:	watering eyes.	
	Skin: Contact with skin does not normally cause immediate irritation. But	
	prolonged contact may result in redness, swelling, skin burns and severe	
	damage.	
	Ingestion: Corrosive if swallowed. Burning, choking, nausea, vomiting,	
	severe pain; Danger of perforation of esophagus and stomach	
	Inhalation: Severe irritation and burning of the nose, throat and respiratory	
	tract.	

Chronic Effects:	Prolonged or repeated overexposures by inhalation or skin or eye contact may result in severe irritation or corrosive effects.  The mucus membranes, the respiratory tract and the digestive system are subject to irritation and corrosive effects from chronic exposure. Changes in pulmonary function may occur, along with chronic bronchitis and emphysema.
Carcinogenetic:	None of this product's components are listed by ACGIH, OSHA, IARC, NIOSH,
	NTP or California Prop 65 as carcinogenic.
Mutagenicity:	Not Available
Reproductive Toxicity:	Not Available

SECTION 12. ECOLOGICAL INFORMATION		
Ecotoxicity:	May be harmful to fish, livestock and wildlife. Non-persistent and non-cumulative when properly applied agronomically.  A toxic hazard to fish. Avoid spills or releases to watercourses.  The products of degradation are less toxic than the product itself.	
Other Adverse Effects:	Not harmful to ozone layer	
Ecotoxicity:	LC50 Pseudokirchneriella subcapitata (Green Algae): 11500 ug/L/126 hrs; static LC50 Gasterosteus aculeatus (Threespine Stickleback): 80000 ug/L/96 hrs; static	

SECTION 13. DISPOSAL CONSIDERATIONS		
General Information:	As packaged, this product is a D002 corrosive waste per 40 CFR 261; applicable to wastes containing this product.	
Disposal Instructions:	Agronomical land application at recommended rates or dispose of in	
	accordance with local/regional/national regulations. Container contents	
	should be completely used and the containers rinsed prior to discard.	
	Rinsate should be treated as a corrosive material. Dispose of in accordance	
	with product characteristics at time of disposal.	

SECTION 14. TRANSPORT INFORMATION		
This material is hazardous as defined by 49 CFR 172.101 by the US Department of Transportation		
Proper Shipping Name:	Corrosive Liquid N.O.S. (Monocarbamide dihydrogensulfate)	
Hazard Class:	8	
UN Identification #:	1760	
Packing Group:	III	
Required Label(s):	Corrosive	
<b>Emergency Response</b>	154	
Guide Number:		
<b>Special Provisions for</b>	Note: DOT corrosive to aluminum. Not regulated if transported by motor	
Transport	carrier or railcar in packaging that will not react or be degraded by this	
	material – 49 CFR 173.154(d).	
Marine Pollutant:	No	

SDS: Phury Chemical Dynamics, Inc.

Rev: 4/9/2014

SECTION 15. REGULATORY INFORMATION		
TSCA Inventory Status	All intentional ingredients listed on the TSCA inventory.	
DSCL (EEC) Status	All intentional ingredients listed on the DSCL inventory.	
United States – SARA Hazard Category:	This product has been reviewed according to the EPA Hazard Categories promulgated under Sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act (SARA) and is considered, under applicable definitions, to meet the following categories:  Fire – No, Pressure – No, Acute – Yes, Chronic – No, Reactive – No	
SARA Title III Information:	This product contains the following substances subject to the reporting requirements of Title III (EPCRA) of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:	
Urea Sulfate	CERCLA RQ (pounds): This product contains no Reportable Quantity (RQ)	
CAS No. 21351-39-3	Substances. However, since spilled material may react with water to release sulfuric acid, an effective RQ of 2040 lbs (161 gallons) should be applied in the event of a spill.  SARA Reporting, 302: No SARA Reporting, 304: No SARA Reporting, 313: No	
Federal Insecticide,	This product is not a pesticide.	
Fungicide, and Rodenticide Act		
State Regulations:	Other state regulations may apply. Check individual state requirements.	

## **SECTION 16. OTHER INFORMATION**

Date of Revision:	4/9/2014, revision prepared in accordance with 29 CFR 1910.1200 Appendix D to meet Global Harmonization Standards.
Disclaimer:	The information contained in this SDS refers only to the specific material designated and does not relate to any process or use with any other materials. This information is based on data believed to be accurate and reliable as of the date hereof. It is intended for use by persons possessing technical knowledge at their own discretion and risk. Because safety standards and regulations are subject to change and because Chemical Dynamics, Inc. has no continuing control over the material, those handling, storing or using the material should satisfy themselves that they have current information regarding the particular way the material is handled, stored or used and that the same is done in accordance with federal, state and local law. No warranty, expressed or implied, and no liability is assumed by Chemical Dynamics, Inc. in conjunction with the use of this information. Nothing herein is to be construed as a recommendation to infringe any patents.

Rev: 4/9/2014